



HD1125 - LAN Printer

Features

1. 203 dpi (8 dots/mm) resolutions; Ultra high print speed 5 ips (127mm/sec).
2. Support Direct Thermal & Thermal Transfer Two Modes.
3. 4 Interface Designed For Multiple Requirements.
4. 120 mm Wide Paper exit for option more wide label roll.
5. External paper holder are optional for industrial-grade large roll.

Specification

Model	HD1125
Dimension	210(W)x180(H)x285(L)
Weight	2.09 Kg
Power Supply	Input : AC 100-240V, Output : DC 24V 2.5A, 60W
Environment	Work Environment : temperature 5~40°C (41~104°F), Humidity 25~85 %
Interface	Serial +USB + Parallel + Ethernet

Print Specification

Dot density	203dots/inch (8 dots/mm)
Print Method	Ribbon / Thermal
Dot Size (WxL)	0.125x0.125mm (1mm=11.8 dots)
Print Speed (inch / Sec)	2~5 inch/s
Maximum print width	108 mm (4.25")
Maximum print length	2286 mm(90")
Pulse execution	1*108 pulse
Thermal film(reliability)	50 KM

Ribbon Specification

Ribbon diameter	Max 67 mm
Ribbon length	300m
Ribbon axis size	1 inch
Ribbon Width	Max 110 mm , Min 30 mm
Ribbon winding method	Outward winding

Paper Specification

Paper roll diameter(max)	127 mm(5")OD
Paper type	Continuous paper, paper with interfaces, folding paper, black mark paper
Paper rolling up method	Printing side outward rolling / inward rolling
Paper width	Max. 120mm(4.72")
(Upper & bottom paper)	Min 20mm(0.78")
The thickness of the paper	Max 0.254 mm
(Upper & bottom paper)	Min 0.06mm
Paper roll axis size	25.4 mm ~ 38(1"~1.5")
Label length	10~2286 mm(0.39"~90")
Gap size	Min 2mm (0.09")
Software	
Editing Software	Nicelabel SE
Driver	Windows 2000, XP, Vista, Windows 7/8/8.1/10, Windows Server 2003 & 2008