

# Laser Scanner SG 7130



## Specifications

Scan Performance	
<b>Scan Mode</b>	All direction , 24 lines (Automatic continuous scanning)
<b>Indicator</b>	Beeper and LED (stand by red, good read green)
<b>Read Rate</b>	2000 scans/sec
<b>Rotate Camera</b>	1±36°
<b>Transfer Rate</b>	RS232baudrate: 2400-38400
<b>Resolution</b>	5mil
<b>Depth of Field</b>	up to 230mm @ 13mil
<b>Light Source</b>	650nm ± 10nm visible laser diode
<b>Print contrast</b>	Above 30% Black
<b>Interface</b>	USB-HID,USB-UART,PS/2,RS232
<b>Decode Type</b>	UPC-A,UPC-E,EAN-13,EAN-8,ISBN/ISSN, Code39, CODABAR Interleaved 2 of 5, Industrial 2 of 5, Chinese 2 of 5, Code128, Code93, Code11 MSI/PIESSEY, UK/PLESSE,UCC/EAN128, China Postage
Electrical	
<b>Input Voltage</b>	+5V DC, 250mA
<b>Output</b>	1.25Watt
<b>Power Source</b>	Keyboard wedge, Rs-232 or USB from host system
<b>Dustproof and waterproof</b>	IP54
<b>Illumination</b>	Max4800LUX
Environmental	
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	-10°C ~ 60°C
<b>Humidity</b>	20% ~ 95% RH (non-condensing)
<b>Drop</b>	1.2m drops on the concrete surface
Mechanical	
<b>Dimensions</b>	112mmL x 102mmW x 147mmH

<b>Weight</b>	Average 360g
<b>Color</b>	White, Black
<b>Cable</b>	2m
<b>Other</b>	
<b>Language</b>	Support multiple kinds of language
<b>Interface Type</b>	RJ-45