

## Barcode Scanner AATPL - 9180



Electrical Specification	
<b>Input voltage:</b>	DC +12V @1.5A
<b>Power:</b>	2.28 w
<b>Operating current:</b>	190mA
<b>Standby current:</b>	160 mA
Scan specification	
<b>Light Source:</b>	650 nm VLD $\pm$ 10nm
<b>Depth of Field:</b>	Up to 250 mm@13 mill/0.33mm, PCS 90%
<b>Scan Mode:</b>	7 directions 24 lines
<b>Scan Rate:</b>	2400scans/sec
<b>Resolution:</b>	5mil/0.127mm
<b>Print Contrast Ratio:</b>	30%
<b>Interface:</b>	RS232,USB,PS/2
<b>Indicator:</b>	LED, beeper(Stand by blue, Good read orange)
<b>Illumination:</b>	up to 4800 LUX
<b>Decode type:</b>	EAN/UPC/JAN + Add-on, ISBN, Code 128, EAN 128, Code 93, Code 39, Code 32, Codabar, Interleaved 2 of 5, MSI-Plessey, GS1 DataBar compliance (symbol 1-9)
Mechanical	
<b>Dimensions:</b>	152mm(Long) x 95 mm(Width) x 152.07mm(Height)
<b>Weight:</b>	690g
Environmental	
<b>Operating Temperature</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temperature:</b>	-10°C ~ 60°C (14°F ~ 140°F)

**Accessories: Scanner, Manual, Cable, Neutral Packing Box**