

Long Range CCD Scanner AATPL -2000



Light Source Type	660 nm visible red LED
Trigger Mode	Manual
Scanning Mode	Single-line scanning
Scanning Speed	300times /sec
Scan Precision	$\geq 4\text{mil}$
Printing Contrast Ratio	The lowest reflectivity difference is 30%.
Bit Error Rate	1/50 million
Environment Luminance	3000-12000 Lux
Depth of field	5 to 630mm
Scanning Angle	$\pm 65^\circ \pm 42^\circ$ (Left and right, front and back, rotation)
Decoding capacity	UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI,
	Code11, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII,
	Codabar, Code93, Discrete2of5, IATA, RSS variants, Codabar, Chinese2of5,

	International general dimensional barcodes, e.g. Inteleaved2/5, Interleaved2of5 and China postal
Electrical parameter	
Input voltage	5VDC±0.25V
Power	250mW (Work): 500mW (momentary maximum)
Current	50mA (Work): 100mA (momentary maximum)
Standby Current	45uA
Prompt Mode	Buzzer and LED indicator
Physical parameter	
Transfer cable interface	USB(standard):PS/2 and RS232 are selectable
Dimension	L*W*H:159*64*85mm
Weight	200g(excluding cables)
Cable standard	Straight line,2m
Interface type	RJ-45 crystal head
Outside material	ABS+PC
Environment parameter	
Temperature	0°C to 50°C(work)¼š-40°C to 60°C(storage)