

Receipt Printer AATPL - POS - 58



item	Parameter	
Print parameter	Printing Method	Thermal Line
	Effective Printing Width	48mm
	Resolution	384 dots/line ¹ / ₄ [^] 8dots/mmi ¹ / ₄ ^E 203dpi ¹ / ₄ ^o
	Printing Speed	70mm/S
	Interface	USB, Serial, Bluetooth
	Line spacing	3.75mmi ¹ / ₄ [^] Can adjust line spacing by commandi ¹ / ₄ ^o
	Line No.	Font A:32 character /Line
		Font B:42 character/Line
Character	Simple, traditional Chinese-16 lines	
Character Size	The standard GB18030 simplified / traditional Chinese characters library	
	ANK characteri ¹ / ₄ ^E Font	
	Ai ¹ / ₄ ^š 1.5×3.0mmi ¹ / ₄ [^] 12×24ç, i ¹ / ₄ ^o Font Bi ¹ / ₄ ^š 1.1×2.1mmi ¹ / ₄ [^] 9×17ç, i ¹ / ₄ ^o Simplified/Traditio nali ¹ / ₄ ^š 3.0×3.0mm(24×24ç, i ¹ / ₄ ^o	
Bar code character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/EastEurope/Iran/WPC1252/P C866/PC852/PC858/IranII/Latvian/Arabic/PT151,1 251/PC737/WPC/1257/ThaiVietnam/PC864/PC100 1/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(P C864)/(Vietnam)/(Thai)
	Bar code	1D.Bar codei ¹ / ₄ ^š UPC-A/UPC- E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D.Bar codei ¹ / ₄ ^š QRCODE

Graphics printing	Graphics printing	Supports bitmap download and print
Power saving Mode	Smart power saving	Support
	Variable speed printing	Support
	Consumption	Support
	Dormancy	Support
Detection	Sensor	Lack of paper detection
Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
	Beep	Lack of paper, printing abnormal alarm
Paper	Type	Thermal
	Width	57.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤40mm
	Feed	Easy ^{1/4} Clamshell feed ^{1/4} %
Print commands	Commands	ESC/POS
Power	Type	Rechargeable Lithium polymer battery
	Capacity	2000mAh/7.4V
	Charger	9.0V/2A
Buffer	Input	4KB
	NV Flash	40KB
Physical features	Weight	200G
	Dimension	114*80*50(MM)
Environment	Operating	Temp ^{1/4} 5 ~ 45°,f ^{1/4} CEHumidity ^{1/4} 10 ~ 80%
	Storage	Temp ^{1/4} -10 ~ 50°,f ^{1/4} CEHumidity ^{1/4} 10 ~ 90% ^{1/4} No Dew ^{1/4} %
Reliability	Print head life	50KM ^{1/4} Printing Density≤12.5i ^{1/4} %
Software	Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1