

| Printer parameters | |
|----------------------------|---|
| Printing method | Thermal line |
| Roll width | 80mm |
| Print width | 72mm |
| Print speed | 60mm/s ADJ |
| Resolution | 203dpi |
| Font | ASCII (16×8、24×12)、GBK (16×16、24×24)、BIG5(16×16、24×24) |
| Printers core life | 50km/100 million pulses |
| Command | ESC/POS |
| Print content | English, numbers, symbols, characters, graphics, one-dimensional bar codes, 2D barcodes |
| Print length on one charge | Next 12.5% print density can print 100-130m |
| Charging method | On/off charge |
| Charging time | 2.5 hours |

| Communication Interface | |
|-------------------------|--|
| Wired interface | TTL/USB |
| Wireless Interface | Bluetooth V2.0 CLASS 2 |
| Physical parameters | |
| Dimensions | 125mm×98mm×55mm |
| Weight | 276g(Including battery, excluding rolls) |
| Other features | |
| Paper loading | Manually loading paper |
| Status Indication | OLED display power shortage, Bluetooth status |
| Environment | Temperature -10 ° C ~ 50 ° C Humidity 20% to 85% |
| Charging environment | Temperature 5 ° C ~ 40 ° C Humidity 20% to 85% |
| Storage Environment | Temperature -20 ° C ~ 70 ° C Humidity 5% to 95% |