

## Receipt Printer AATPL - POS - 300



	Printing Method	Thermal Line
<b>Print parameters</b>	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line(8dots/mm,203dpi)
	Print speed	300mm/Second
	Interface	USB+RS232+LAN, USB+RS232+Wi-Fi, USB+Bluetooth, USB+GPRS(Comin
	Line Spacing	3.75mm(Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines/Simple, traditional Chinese-24 lines
	Character	standard GB18030 simplified/traditional Chinese Fonts
	Character Size	ANK character, Font A:1.5×3.0mm(12×24 dots);Font B:1.1×2.1mm(9×17 d
<b>Bar code Character</b>	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/Eas
	Barcode Symbolologies	1D bar code:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/C 2D barcode:QRCODE
<b>Graphics printing</b>	Graphics printing	Supports bitmap download and print(each bitmap size Max.20K)
<b>Cutter</b>	Cutter Function	Full cut/Half cut
<b>Print commands</b>	Commands	ESC/POS
<b>Paper</b>	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm
	Feed method	Easy feed(Clamshell feed)
<b>Power</b>	Power Adaptor	Input: AC 110V/220V,50r/2ž60Hz, Output: DC 24V/2.5A
	Cash	DC 24V/1A

	Drawer output	
<b>Buffer</b>	Input Buffer	2048K bytes
	NV Flash	256K bytes
<b>Physical characteristics</b>	Weight	1.3KG
	Dimension	185*145*135(MM)
<b>Environment</b>	Working	Temp:5 ~ 45 <sup>o</sup> ,f, Humidity <sup>1</sup> / <sub>4</sub> š10 ~ 80%
	Storage	Temp:-10 ~ 50 <sup>o</sup> ,f, Humidity <sup>1</sup> / <sub>4</sub> š10 ~ 90%(No dew)
<b>Reliability parameter</b>	Print Head Life	150KM(print density≤12.5)
	Cutter Life	1500,000times
	Driver	Android,IOS,Linux, Win2000, Win2003, WinXP, Win7, Win8, Win8.1
<b>Software</b>		